

IN THE CLAIMS:

Please add the following new claims to the application:

Claim 1. (Original) Apparatus for use in cutting a plug from hard material of the earths surface including rock and like to make a post hole in said material, said apparatus comprising:

a drive shaft having a longitudinal axis, means at one end of said drive shaft for connecting the same to a power driven unit and a cutting head mounted on and projecting from an end of shaft opposite said one end, said cutting head including a side wall defining a tubular body disposed co-axial with said drive shaft and terminating in a free outer end spaced a selected distance from the end of said shaft opposite said one end, a plurality of teeth mounted on said wall and extending from the free end thereof in an array about the periphery of an opening of selected diameter into a cavity defined by said side wall, said cavity being of selected depth for receiving therein a plug cut from said material by said teeth as said tubular body is rotated about said axis, said side wall having at least one opening extending there through forming a cutaway portion that includes an edge, said edge having length in a direction parallel to said axis for scraping debris from the wall of the post hole during rotation of the cutting head about said axis.

Claim 2. (New) An auger apparatus for use in cutting a plug from hard material of the earths surface including rock and like to make a post hole in said material, said apparatus comprising:

a cutting head including a side wall defining a tubular body and end plate;
means at one end of said cutting head for connecting said end plate to a power driven unit;
a plurality of teeth mounted on said wall extending from the free end thereof in an array about the periphery of an opening of selected diameter into a cavity defined by said side wall, said cavity being of selected depth for receiving therein a plug cut from said material by said teeth as said tubular body is rotated about an axis, said side wall including an opening defining a cutaway portion including lateral edges.

Claim 3. (New) The auger apparatus of claim 2, further including a drive shaft mounted in cooperative engagement with said means for connecting to a power driven unit and projecting from an end of said cutting head opposite said teeth.

Claim 4. (New) The auger apparatus of claim 3, wherein said drive shaft having a longitudinal axis includes means at one end of said drive shaft for connecting the same to a power driven unit disposed co-axially with said cutting head and terminating in a free outer end spaced a selected distance from the end of said shaft opposite said one end.

Claim 5. (New) The auger apparatus of claim 2, wherein said means for connecting includes an end plate connecting to at least a portion of said side wall forming said tubular body of said cutting head opposite said teeth, joining at least two points of said side wall.

Claim 6. (New) The auger apparatus of claim 2, wherein said body includes a cutaway portion extending around the periphery thereof a selected length forming an edge extending along a portion of said side wall generally parallel to said axis.

Claim 7. (New) The auger apparatus of claim 2, wherein said body includes a cutaway portion extending around the periphery thereof a selected length forming an edge extending along a portion of said side wall generally parallel and vertical to said axis.

Claim 8. (New) The auger apparatus of claim 2, wherein said body includes a cutaway portion extending around the periphery thereof a selected length forming an edge extending along a portion of said side wall generally disposed at an angle and generally parallel to said axis.

Claim 9. (New) The auger apparatus of claim 5, further comprising a pilot drill extending from an end plate, said pilot drill disposed within said tubular body and extending in axial alignment therewith.

Claim 10. (New) The auger apparatus of claim 9, wherein said pilot drill extending pass said teeth extending from said lower peripheral edge of said cutting head.

Claim 11. (New) The auger apparatus of claim 9, wherein said pilot drill includes a removable tip;.

Claim 12. (New) The auger apparatus of claim 9, including means for reinforcing and bracing said pilot drill shaft mounting to said bottom surface of said end plate.-

Claim 13. (new) The auger apparatus of Claim 12, wherein said means for reinforcing and bracing said pilot drill shaft comprises at least one reinforcing member extending from said bottom surface of said mounting end plate and attaching to at least one selected point of said pilot drill shaft.

Claim 14. (new) The auger apparatus of Claim 12, wherein said means for reinforcing and bracing said pilot drill shaft comprises a plurality of tapered support plates having a broad base extending from said bottom surface of said mounting end plate and a tapered end attaching to said selected point of said pilot drill shaft.-

Claim 15. (new) The auger apparatus of Claim 14, wherein said tapered support plates are welded all along the edge to said pilot drill shaft extending to a point near said drill tip.

Claim 16. (new) The auger apparatus of Claim 9, wherein said distal end of said pilot drill shaft ends in a short cylindrical collar including means for removably attaching said drill tip.

Claim 17 (new) The auger apparatus of Claim 2, said tubular body further comprising a double side wall having an overlapping lateral cutaway portion staggered forming a double edge.

Claim 18. (New) The auger apparatus of Claim 2, said means for connecting to a power unit including a quick disconnect assembly.

Claim 19. (New) The auger apparatus of Claim 2, wherein said cutaway portion of said tubular body extends around the periphery thereof a selected length extending from a lower peripheral cutting edge toward said end plate, said cutaway portion forming at least one lateral cutting edge.

Claim 20. (New) The auger apparatus of claim 9, wherein means for cooperatively engaging a drive shaft extends from a top surface of said end plate and comprises a socket shaped for cooperatively engaging a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end cooperatively engaging said socket of said end plate and having an opposing distal drive end extending therefrom.

Claim 21. (New) An auger apparatus comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining a side wall connecting to an end plate, said hollow cylindrical body defining an upper peripheral edge and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

said end plate of said hollow cylindrical body extending across joining said side wall;

a drive shaft having a diameter less than said cutting head, said shaft including a proximal end connecting to said end plate and having an opposing distal drive end extending therefrom;

means for connecting said distal end of said drive shaft to a power unit; and

a cutaway portion of the body extending around the periphery thereof a selected length forming a side wall edge extending along said cutaway portion.

Claim 22. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining a tubular side wall connecting to an end plate extending across an upper peripheral edge of said hollow cylindrical body and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end connecting to said end plate and having an opposing distal drive end extending therefrom; and

a pilot drill extending from an end plate, said pilot drill disposed within said cylindrical hollow cutting head and extending in axial alignment with said drive shaft;

said pilot drill extending past said teeth extending from said lower peripheral edge of said cutting head; and

a cutaway portion of the body extending around the periphery thereof a selected length forming an opening and defining a side wall edge extending along a portion of said side wall from along a portion of the bottom above said teeth toward said end plate.

Claim 23. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining side wall connecting to an end plate extending across an upper peripheral edge of said hollow cylindrical body and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

said end plate extending across said side wall and including at least one opening there through;

a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end connecting to a top surface of said end plate and having an opposing distal drive end extending therefrom; and

a cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to a selected point of said end plate, said cutaway portion forming a lateral side wall edge.

Claim 24. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining side wall connecting to an end plate extending across said side wall enclosing at least a portion of said hollow

cylindrical body, and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end connecting to a top surface of said end plate and said drive shaft having an opposing distal drive end extending therefrom; and

at least one cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to a selected point of said end plate, said cutaway portion forming a lateral side wall edge.

Claim 25. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining side wall connecting to an end plate extending between said side wall enclosing at least a portion of a top end of said hollow cylindrical body, and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

said side wall of said hollow cylindrical body including at least one opening therein;

a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end connecting to a top surface of said end plate and having an opposing distal drive end extending therefrom; and

a pilot drill extending from a bottom surface of said end plate, said pilot drill disposed within said cylindrical hollow cutting head and extending in axial alignment with said drive shaft;

said pilot drill having a removable tip;

said pilot drill extending pass said teeth extending from said lower peripheral edge of said cutting head; and

a cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to a selected point of said end plate, said cutaway portion forming an angled lateral side wall edge.

Claim 26. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining side wall connecting to an end plate extending across side wall enclosing at least a portion of a top end of said hollow cylindrical body, and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end connecting to a top surface of said end plate and having an opposing distal drive end extending therefrom; and

a cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to a selected point of said end plate, said cutaway portion forming a lateral vertical side wall edge.

Claim 27. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining side wall connecting to an end plate extending across side wall enclosing at least a portion of a top end of said hollow cylindrical body, and a lower open end defining a lower peripheral cutting edge including a plurality of teeth extending from said lower peripheral edge;

means for cooperatively engaging a drive shaft extending from a top surface of said end plate;

a cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to said end plate, said cutaway portion forming a lateral side wall edge.

Claim 28. (New) An auger apparatus, comprising:

a cylindrical hollow cutting head comprising a hollow cylindrical body defining side wall connecting to an end plate extending across and joining said side wall enclosing at least a portion of said hollow cylindrical body, said cylindrical hollow cutting head having a lower open end defining a lower peripheral cutting edge including a plurality of teeth projecting from said lower peripheral cutting edge;

means for cooperatively engaging a drive shaft extending from a top surface of said end plate;
a cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to said end plate, said cutaway portion forming a lateral side wall edge.

Claim 29. (New) The auger apparatus of Claim 28, including means for reinforcing and bracing said pilot drill shaft mounting to said bottom surface of said end plate.

Claim 30 (new) The auger apparatus of Claim 28, said hollow cylindrical body further comprising a double side wall having an overlapping lateral cutaway portion staggered forming a double side wall edge.

Claim 31. (New) The auger apparatus of Claim 28, said means for cooperatively engaging a drive shaft including a quick disconnect assembly.

Claim 32. (New) An auger apparatus comprising:

a cylindrical hollow cutting head for removing plugs of hard material from post holes comprising a hollow cylindrical body defining side wall connecting to an end plate, said hollow cylindrical body defining an upper peripheral edge and a lower open end defining a lower peripheral cutting edge including a plurality of removable teeth extending from said lower peripheral edge;

said end plate extending across said hollow cylindrical body joining said side wall and covering at least a portion thereof;

a drive shaft having a diameter less than said cutting head, said drive shaft including a proximal end connecting to a top surface of said end plate and having an opposing distal drive end extending therefrom;

means for connecting said distal drive end of said shaft to a drive shaft of a power unit; and

at least one cutaway portion of the body extending around the periphery thereof a selected length forming an opening extending along a portion of said side walls extending from said lower peripheral cutting edge to said end plate, said cutaway portion forming at least one lateral side wall

edge.

Claim 33. (New) The auger apparatus of claim 28, further comprising a pilot drill bit including a pilot drill bit shaft and tip disposed within said cylindrical hollow cutting head, said pilot drill bit shaft mounting to a bottom surface of said mounting end plate.